



MATERIAL SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

- **Trade Name** DURA LACQUER THINNERS A (DI004)
- **Synonyms** Not available..
- **Dura Paints cc** 5 Wakefield Road; Founders View South; Edenvale; 1610; South Africa.

2. COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS#	% BY WEIGHT	EXPOSURE LIMITS
Aromatics	108-88-3	19-26	ACGIH TLV (USA, 2003) TWA: 50ppm 8 hrs OSHA PEL Z2 (USA, 2003) TWA: 200ppm 8 hrs CEIL: 300ppm NIOSH (USA, 1997) STEL: 150ppm 15 min STEL: 560 mg/m ³
	1330-20-7	7-12	ACGIH TLV (USA, 2003) TWA: 100ppm 8 hrs STEL: 150ppm 15min OSHA PEL Z1 (USA, 1993) : 100ppm :435mg/m ³ NIOSH (USA, 1997) STEL: 150ppm 15 min STEL: 665mg/m ³ 15 min
Alcohol	71-23-8		ACGIH TLV (USA, 2003) STEL: 250ppm 15 min TWA: 200ppm 8 hrs OSHA PEL Z1 (USA, 1993) TWA: 200ppm 8 hrs
		26	TWA: 500mg/m ³
26		17	ACGIH TLV (USA, 2002) TWA: 500ppm 8 hrs TWA: 1188mg/m ³ 8 hrs STEL: 750ppm 15 min STEL: 1782mg/m ³ OSHA (USA, 2002) TWA: 750ppm 8 hrs TWA: 1800mg/m ³ 8 hrs STEL: 1000ppm 15min STEL: 2400mg/m ³ 15min

NAME	CAS#	% BY WEIGHT	EXPOSURE LIMITS
		6	ACGIH TLV (USA, 2003) TWA: 20ppm 8 hrs OSHA PEL Z1 (USA, 1993) : 50ppm : 240mg/m ³ NIOSH REL (USA, 1997). SKIN REL: 5ppm 40 hrs REL: 24mg/m ³
Hydrocarbon	611-14-3 78-92-2	1-4 3	Not Available. OSHA PEL Z1 (USA, 2002) TWA: 150ppm 8hrs TWA: 450mg/m ³ hrs

3. HAZARDS IDENTIFICATION

Physical state and Appearance:

Liquid.

Emergency overview:

WARNING!
 FLAMMABLE LIQUID AND VAPOUR.
 VAPOUR MAY CAUSE FLASH FIRE.
 RISK OF SERIOUS DAMAGE TO EYES.
 HARMFUL BY INHALATION.
 REPEATED EXPOSURE MAY CASUE SKIN CRYNESS & CRACKING.

Keep away from heat, sparks and flame. Avoid contact with eyes, skin and clothing. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Routes of entry:

Eye contact. Ingestion. Inhalation.

Potential acute health effects:

Eyes:

Risk of serious damage to eyes.

Skin:

Repeated exposure may cause skin dryness or cracking.

Inhalation:

Inhalation can be harmful.

Ingestion:

Hazardous in case of ingestion

Potential chronic health:

CARCINOGENIC EFFECTS classified A4 (Not classifiable for human or animal).
 By ACGIH, 3 (not classifiable for human) by IARC [Toluene].
 Classified A\$ (Not classifiable for human or animal)by ACGIH,3 (Not classifiable for human) by IARC [xylenes].
 Classified None, by OSHA, [Acetone].
 Classified A4 (not classifiable for human or animal)by ACGIH, D (Not classifiable for human or animal), by EPA [Acetone].
 Classified A3 (Proven for animal) by ACGIH [Propyl alcohol].

Classified None, by OSHA, NONE. By NIOSH [propyl alcohol].
classified 4 (probably not for human) by IARC, none, by NIOSH
[butan-2-ol].
Classified none, by NIOSH. Classified None by NIOSH[2-
Methylpropan-1-ol]. Classified A3 (proven for animal) by ACGIH
[Glycol ether].
MUTAGENIC EFFECTS: Non-mutagenic for bacteria and/or yeast
[Xylenes].
TERATOGENIC EFFECTS classified none. For human [Acetone].

**Medical conditions aggravated
by overexposure:** No data available.

Overexposure/signs/symptoms: No data available.

4. FIRST AID MEASURE

Eye contact: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.

Skin contact: In case of skin contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention if symptoms appear.

Inhalation: If inhaled, remove to fresh air and allow victim to rest. If not breathing, administer artificial respiration. If breathing is laboured, give oxygen. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. If large quantities of this material are swallowed, seek immediate medical attention.

Notes to physician: Support respiratory and cardiovascular function.

5. FIRE FIGHTING MEASURES

Flammability of the product:	Flammable
Autoignition temperature:	The lowest known value is 238°C [Glycol ether]
Flash points:	Closed cup: <0°C
Flammable limits:	The greatest known range is LOWER: 1.1% UPPER: 14.7% [Glycol ether]
Products of combustion:	These products are carbon oxides [CO, CO ₂]
Fire hazards in the presence of various substances:	Flammable in presence of open flames, sparks and static discharge of heat of oxidizing materials, of combustible materials, of combustible materials, of reducing materials, of alkalis.
Explosive hazards in the presence of various substances:	Not available.
Fire fighting media and Instructions:	SMALL FIRE: Use DRY chemical powder LARGE FIRE: Use water spray or fog. Cool containing vessels with jet in order to prevent pressure build-up, autoignition or explosion.
Protective clothing (fire):	Be sure to use an approved/certified respirator or equivalent.
Special remarks on fire hazards:	Explosive in the form of vapour when exposed to heat or flame. Vapour may travel considerable distance to source of ignition and flash back. When heated to decomposition it emits acrid smoke and irritating fumes.
Special remarks on explosion Hazards:	No additional remark.

6. ACCIDENTAL RELEASE MEASURES

Small spill or leak:	Absorb with an inert dry material and place in an appropriate waste disposal container.
Large spill or leak:	Poisonous flammable liquid, insoluble or very slightly soluble in water. Keep away from heat. Keep away from sources of Ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. DO NOT get water inside the container. DO NOT touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all sources of ignition. Call for assistance on disposal.

7. HANDLING AND STORAGE

Handling:	Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling) equipment
------------------	---



Storage:

Store in a segregated and approved area. Keep container in a cool, well ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flames)

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapour below their respective threshold limit values. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal protection

Eyes:

Splash goggles.

Body:

Chemical resistant protective suite.

Respiratory:

Vapour respirator. Be sure to use an approved/certified or equivalent. Wear appropriate respirator when ventilation is inadequate.

Hands:

Butyl rubber gloves.

Feet:

Chemical resistant safety boots.

Protective clothing:

Splash goggles. Full chemical resistant protective suit. Vapor respirator. Butyl gloves. Chemical resistant boots.

Personal protection in case of large spills:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling the product.

NAME

EXPOSURE LIMITS

Aromatics

ACGIH TLV (USA, 2003)

TWA: 50ppm 8 hrs

OSHA PEL Z2 (USA, 2003)

TWA: 200ppm 8 hrs

CEIL: 300ppm

NIOSH (USA, 1997)

STEL: 150ppm 15 min

STEL: 560 mg/m³

ACGIH TLV (USA, 2003)

TWA: 100ppm 8 hrs

STEL: 150ppm 15min

OSHA PEL Z1 (USA, 1993)

: 100ppm

:435mg/m³

NIOSH (USA, 1997)

STEL: 150ppm 15 min

STEL: 665mg/m³ 15 min

Alcohol

ACGIH TLV (USA, 2003)

STEL: 250ppm 15 min

TWA: 200ppm 8 hrs

OSHA PEL Z1 (USA, 1993)

TWA: 200ppm 8 hrs

TWA: 500mg/m³

(table continues on next page)



<u>NAME</u>	<u>EXPOSURE LIMITS</u>
Actives	ACGIH TLV (USA, 2002) TWA: 500ppm 8 hrs TWA: 1188mg/m ³ 8 hrs STEL: 750ppm 15 min STEL: 1782mg/m ³ OSHA (USA, 2002) TWA: 750ppm 8 hrs TWA: 1800mg/m ³ 8 hrs STEL: 1000ppm 15min STEL: 2400mg/m ³ 15min ACGIH TLV (USA, 2003) TWA: 20ppm 8 hrs OSHA PEL Z1 (USA, 1993) : 50ppm : 240mg/m ³ NIOSH REL (USA, 1997). SKIN REL: 5ppm 40 hrs REL: 24mg/m ³
Hydrocarbon	Not Available. OSHA PEL Z1 (USA, 2002) TWA: 150ppm 8hrs TWA: 450mg/m ³ hrs

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State & Appearance	: Liquid
Colour	: Clear, colourless (Light)
Odour	: No data available
Taste	: No data available
Molecular Weight	: Not applicable
Molecular Formula	: Not applicable
PH (1% Soln/Water)	: Neutral
Boiling/condensation Point	: 58°C
Melting / freezing point	: May start to solidify at -70°C based on data for: Glycol ether. weighted average: -103.95°C.
Critical temperature	: No data available.
Specific gravity	: 0.801 (water=1)
Volatility	: 100% (v/v) (propyl alcohol). Weighted average: 100% (v/v) 100% (w/w) (propyl alcohol) weighted average: 100% (w/w)
Odor threshold	: the lowest known value is 0.1ppm (glycol ether). Weighted average: 15.97ppm
Evaporation threshold	: 1.109 compared to Butyl acetate
VOC	: 100 (%)
LogK_{ow}	: No data available..
Ionicity (in water)	: No data available
Dispersion properties	: Is not dispersed in cold water, hot water, methanol, diethyl ether, n-octanol. See solubility in methanol, diethyl ether, n-octanol.
Solubility	: Soluble in n-octanol, diethyl ether, methanol...

10. STABILITY AND REACTIVITY

Stability and reactivity	: The product is stable.
Conditions of instability	: Sparks, flames, heat and other ignition sources.
Incompatibility with various substances	: Reactive with oxidizing agents, reducing agents, organic materials, acids, alkalis and metals.
Hazardous decomposition products	: No data available
Hazardous polymerization	: Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicity to animals	: Acute oral toxicity (LD50): 1441mg/kg [Rat] (calculated value for mixture) Acute dermal toxicity (LD50): 220mg/kg [Rabbit] (Glycol ether) Acute toxicity of the gas (LC50): 450 ppm 4 hour(s) [Rat]. (Glycol ether)
Chronic effects on humans	: CARCINOGENIC EFFECTS classified A4 (Not classifiable for human or animal). By ACGIH, 3 (not classifiable for human) by IARC [Toluene]. Classified A\$ (Not classifiable for human or animal)by ACGIH,3 (Not classifiable for human) by IARC [xylenes]. Classified None, by OSHA, [Acetone]. Classified A4 (not classifiable for human or animal)by ACGIH, D (Not classifiable for human or animal), by EPA [Acetone]. Classified A3 (Proven for animal) by ACGIH [Propyl alcohol]. Classified None, by OSHA, NONE. By NIOSH [propyl alcohol]. classified 4 (probably not for human) by IARC, none, by NIOSH [butan-2-ol]. Classified none, by NIOSH. Classified None by NIOSH[2-Methylpropan-1-ol]. Classified A3 (proven for animal) by ACGIH [Glycol ether]. MUTAGENIC EFFECTS: Non-mutagenic for bacteria and/or yeast [Xylenes]. TERATOGENIC EFFECTS classified none. For human [Acetone].
Other toxic effects on humans	: No additional remark
Special remarks on toxicity to animals	: No additional remark.
Special remarks on chronic effects on humans	: Inhalation of vapours may cause dizziness, an irregular heartbeat, narcosis, nausea or asphyiation (Toluene)
Special remarks on other toxic effects on humans	: No additional remark.



12. ECOLOGICAL INFORMATION

Ecotoxicity : No data available

BOD and COD : No data available

Biodegradable/OECD : No data available

Mobility : No data available

Products of degradation : these products are carbon oxides (CO, CO₂) and water

Toxicity of the products of biodegradation : No data available


Special remarks on the products of biodegradation : No food chain concentration potential (Propyl alcohol)

13. DISPOSAL CONSIDERATIONS

Waste information : Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Waste stream : No data available.

14. TRANSPORT INFORMATION

Regulatory information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
DOT Classification	UN 1993	Flammable liquid N.O.S	ADR CLASS 3: Flammable liquid.	II		Reportable quantity 100 lbs. (45.36 kg)
TDG Classification	UN 1993	Flammable liquid N.O.S	ADN CLASS 3: Flammable liquid.	II		
IMDG Classification	UN 1993	Flammable liquid N.O.S	IMDG CLASS 3: Flammable liquid.	II		
IATA-DGR Classification	UN 1993	Flammable liquid N.O.S	IATA CLASS 3: Flammable liquid.	II		


15. REGULATORY INFORMATION



HCS Classification	: HCS Class: Flammable liquid having flash point lower than 37.8°C cCass: irritating substance.
U.S. Federal regulations	<p>: TSCA 4(a) proposed test rules: Butan-2-ol TSCA5(e) substance consent order: Aliphatic ketone; 2-Methylpropan-1-ol TSCA 8(a) PAIR: Trimethyl benzene (isomers); Butan-2-ol; 2-Methylpropan-1-ol</p> <p>TSCA8(a) IUR: Aliphatic ketone; 2-Methylpropan-1-ol TSCA 8(b) inventory: Toluene; Xylenes; Ethyl toluene; trimethyl benzene (isomers), Aliphatic ketone; propyl alcohol; butan-2-ol; 2-Methylpropan-1-ol; Glycol ether TSCA 8(d) H and S data reporting; Toluene; xylenes; Butan-2-ol; Glycol ether TSAC 12(b) one time export; Aliphatic ketone</p> <p>SARA 302/304/311/312 extremely hazardous substances: No reports were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: Butan-2-ol, 2-Methylpropan-1-ol SARA 311/312 MSDS distribution- chemical inventory – hazardous identification: Butan-2-ol; Fire hazard, immediate (acute) health Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard; 2-Methylpropan-1-ol: Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard. SARA 313 toxic chemical notification and release reporting: Xylenes 9.996%; Butan-2-ol 3.1482% Clean water act (CWA) 307: Toluene Clean water act (CWA) 311: Toluene; xylenes. Clean water act (CAA) 112 accidental release prevention: Toluene; xylenes Clean water act (CAA) 112 regulated flammable substances: No products were found. Clean water act (CAA) 112 regulated toxic substances: No products were found.</p>
State regulations	<p>: Connecticut hazardous material survey: propyl alcohol Illinois toxic substances disclosure to employee act: Glycol ether. Illinois chemical safety act: Propyl alcohol; Glycol ether. Rhode island RTK hazardous substances: Toluene; Trimethyl benzene (isomers), Aliphatic Ketone; propyl alcohol; Butan-2-ol; 2-Methylpropan -1-ol, Glycol ether. Pennsylvania RTK: Toluene; Xylene (environmental hazard); Trimethyl benzene (isomers), Aliphatic ketone; (environmental hazard), Propyl alcohol; Butan-2-ol (environmental hazard, generic environmental hazard); 2- methylpropan-1-ol:(environmental hazard, generic environmental hazard); Glycol ether. Florida: Toluene; Trimethyl benzene (isomers); Aliphatic ketone; Propyl alcohol; Butan-2-ol; 2-methylpropan-1-ol. Minnesota: toluene; Xylenes; Trimethyl benzene (isomers); Aliphatic; Propyl alcohol; butan-2-ol; 2-methylpropan-1-ol; Glycol ether.</p>

Michigan critical material: Toluene; xylenes.
 Massachusetts RTK: Toluene, xylenes, trimethyl benzene (isomers), Aliphatic ketone; Propyl alcohol, Butan-2-ol; 2-methylpropan-1-ol, Glycol ether.
 Massachusetts spill list: Glycol ether.
 New Jersey: Toluene; Xylenes; Aliphatic Ketone; Butan-2-ol; 2-methylpropan-1-ol; Glycol ether.
 New Jersey spill list – Toluene; xylenes; Trimethyl benzene (isomers); Aliphatic ketone; Propyl alcohol; Butan-2-ol, 2-Methylpropan-1-ol.
 Louisiana spill reporting: propyl alcohol; Glycol ether
 California prop 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which could require a warning under the statute: Toluene.
 California prop 65 (no significant risk level): Toluene: 7mg/day (value), 13mg/day (inhalation).
 California prop 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Toluene

EU regulations
Hazardous symbol(s)



Classification

: Highly flammable

Risk phrases

: R11 – Highly flammable
 R20 – Harmful by inhalation
 R41 – Risk of serious damage to eyes
 R66 – Repeated exposure may cause skin dryness or cracking

Safety phrases

: S9 – Keep container in well ventilated place.
 S16 – Keep container away from sources of ignition – No smoking.
 S26 – In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 S39 – Wear eye/face protection
 S60 – This material and its container must be disposed of as hazardous waste.

ENIECS Number

: 200-746-9 (Propyl alcohol), 200-662-2 (Acetone), 203-625-9 (toluene), 215-535-7 (xylene), 203-905-0 (Ethylene glycol monobutyl ether), 201-255-1 (Ethyl methyl benzene), 201-158-5 (butan-2-ol)

16 OTHER INFORMATION

National Fire Protection Association (U.S.A.) :

References

- Manufacturers Material Safety Data sheet..
- BDH; Hazard Data disks, Version 3
- RTECHS: National Institute for Occupational Safety and Health, Issue: 97-3 (august 1997).
- CESARS: Chemical Evaluation and Retrieval System, Produced by: Ontario

Ministry of Environment and Michigan Department of Natural Resources,
Issue: 97-3 (August,1997).

- CHEMINFO: Canadian Centre for Occupational Health and Safety, Issue:
97-3 (August 1997). – BDH; Hazard Data Disk, Version 3. – CESARS:
Chemical Evaluation and Retrieval System, Produced by: Ontario Ministry
of Environment and Michigan Department of Natural Resources, Issue 97-
3 (August 1997).

- TOMES Plus System: Toxicology, Occupational Medicine &
Environmental Series: incorporating: - MEDITEX, HAZARDTEXT,
1st Medical Response Protocols, INFOTEXT, HSDB, CHRIS,
OHM/TAD, IRIS, NIOSH Pocket Guide, RTECS, NJ Facts Sheets,
North American Emergency Response Guides, REPROTEXT,
REPROTOX, TERIS, Shepard's Catalog of Teraogenic Agents.
- LOLI Database: The regulated List of Lists.

Other special considerations : No additional remarks.

Date of issue : 07/04/2010

Version

Verified by

END OF MSDS

DISCLAIMER: All information is given in good faith, but without guarantee in respect of accuracy and no responsibility is
accepted for errors or omissions or the consequences thereof. For the current version of this MSDS please download from the Dura
Paints website at www.durapaints.co.za.